



ZPMV8.E170640 Wiring, Printed Certified for Canada - Component

For enhanced search functionality, please visit UL's [iQ™ Family of Databases](#).

Click on a product designation for complete information.

[Page Bottom](#)

Wiring, Printed Certified for Canada - Component

[See General Information for Wiring, Printed Certified for Canada - Component](#)

GLOBAL CIRCUITS BOARD CO LTD

E170640

Room C, 8Th Fl, Manning Ind Bldg

118 How Ming St, Kwun Tong

Kowloon, HONG KONG

Type	Cond Width				Max		Max		Flame	Meets	C
	Min	Edge	Cond	SS/	Area	Solder		Oper			
						Diam	Limits				
	mm(in)	mm(in)	mic(mil)	DS	mm(in)		C	sec			
Multilayer printed wiring boards.											
GMA1	0.10 (0.004)	0.30 (0.012)	17 (0.67) Int:68	DS	38.1 (1.5)	260	20	130	V-0	All	-
GMH1	0.10 (0.004)	0.30 (0.012)	17 (0.67) Int:68	DS	38.1 (1.5)	260	20	130	V-0	All	-
Single layer printed wiring boards.											
GA1	0.10 (0.004)	0.30 (0.012)	17 (0.67)	DS	38.0 (1.5)	260	20	130	V-0	All	-
GA10	0.53 (0.021)	1.60 (0.063)	34 (1.34)	SS	25.4 (1.0)	260	10	105	V-0	All	-
GA11	0.13 (0.005)	0.39 (0.015)	34 (1.34)	SS	25.4 (1.0)	260	10	130	V-0	All	-
GA2	0.10 (0.004)	0.30 (0.012)	17 (0.67)	SS	38.0 (1.5)	260	20	130	V-0	All	-
GA3	0.53 (0.021)	1.60 (0.063)	34 (1.34)	SS	25.4 (1.0)	260	15	105	V-0	All	-
GA4	0.53 (0.021)	1.60 (0.063)	34 (1.34)	SS	25.4 (1.0)	260	10	130	HB	All	-
GA5	0.13 (0.005)	0.39 (0.015)	34 (1.34)	DS	25.4 (1.0)	260	10	130	V-0	All	-
GA6	0.13 (0.005)	0.39 (0.015)	34 (1.34)	DS	25.4 (1.0)	260	10	130	V-0	All	-
GA7	0.10 (0.004)	0.30 (0.012)	34 (1.34)	DS	38.0 (1.5)	260	20	130	V-0	All	-
GA8	0.13 (0.005)	0.39 (0.015)	34 (1.34)	SS	25.4 (1.0)	260	10	105	V-0	All	-
GA9	0.53 (0.021)	1.60 (0.063)	34 (1.34)	SS	25.4 (1.0)	260	10	105	HB	All	-
GC2	0.1 (0.004)	0.1 (0.004)	34.3 (1.35)	DS	9.4 (0.4)	260	10	130	V-0	All	-
GC2D	0.10 (0.004)	0.35 (0.014)	17 (0.67)	SS	12.95 (0.5)	260	10	130	V-0	All	-
GC4D	0.10 (0.004)	0.18 (0.007)	17 (0.67)	DS	25.4 (1.0)	260	20	120	V-0	All	-
GC4E	0.10 (0.004)	0.18 (0.007)	17 (0.67)	DS	25.4 (1.0)	288	20	130	V-0	All	-
GH1	0.10 (0.004)	0.30 (0.012)	17 (0.67)	DS	38.0 (1.5)	260	20	130	V-0	All	-
GH2	0.10 (0.004)	0.30 (0.012)	17 (0.67)	SS	38.0 (1.5)	260	20	130	V-0	All	-



Marking: Company name or tradename "GCB", type designation and Recognized Component Mark for Canada, . May be followed by a suffix to denote factory identification.

[Last Updated](#) on 2014-01-10

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".